

## **CL4NX Plus Cutter Comparison**







		GUILLOTINE CUTTER	ROTARY CUTTER
Part Number		WWCL05100	WWCLP5500
Туре		Guillotine Cutter - A vertical blade between two parallel uprights descend to cut a label.	Rotary Cutter - A small circular blade on a track to create perfectly straight cuts. The sharp blade rotates as it rolls over the media.
Supported Print Resolutions		203, 305, 609 dpi	203, 305, 609 dpi
Print Modes		"Cutter" and "Cut & Print" only	"Cutter" and "Cut & Print" only Note: Rotary Cutter and RFID combination is not supported. Error will occur.
External Dimensions:		10.67" W x 18.82" D x 12.64" H (271mm W x 478mm D x 321mm H) (excluding protrusion)	10.67" W x 19.53" D x 12.64" H (271mm W x 496mm D x 321mm H) (excluding protrusion)
Height with Cover Open:		22.80" (579mm)	22.80" (579mm)
Height of Media Discharge Outlet:		4.25" (108mm)	4.25" (108mm)
Weight:		Approx. 35.71 lbs. (16.2 kg) (excluding media, ribbon and options)	Approx. 39.24 lbs. (17.8 kg) (excluding media, ribbon and options)
Warranty		300,000 cuts (1 year)	500,000 cuts (1 year)
Field Installable		Yes	Yes
Media Thickness		0.0024" to 0.011" (0.060 to 0.268mm)	0.0024" to 0.011" (0.060 to 0.268mm)
Media Length	203 dpi	0.67" to 98.21" (0.79" to 98.43" with liner) 17mm to 2497mm (20mm to 2500mm with liner)	1.18" to 98.31" (1.30" to 98.43" with liner) 30mm to 2497mm (33mm to 2500mm with liner)
	305 dpi	0.67" to 58.94" (0.79" to 19.69" with liner) 17mm to 1497mm (20mm to 1500mm with liner)	1.19" to 58.94" (1.30" to 98.43" with liner) 30mm to 1497mm (33mm to 1500mm with liner)
	609 dpi	0.67" to 15.63" (0.79" to 15.75" with liner) 17mm to 397mm (20mm to 400mm with liner)	1.19" to 15.63" (1.30" to 15.75" with liner) 30mm to 397mm (33mm to 400mm with liner)
Media Width	All dpi	0.87" to 5.04" (0.98" to 5.16" with liner) 22mm to 128 mm (25mm to 131mm with liner)	0.87" to 5.04" (0.98" to 5.16" with liner) 22mm to 128mm (25mm to 131mm with liner)
Media Type		Hang tags, cardstock, and liner	High volume hang tags, cardstock, liner, and thick & thin synthetic materials (i.e. Tyvek)
Recommended Applications		<ul> <li>Compliance labeling</li> <li>Rating plates, asset tracking, shipping</li> <li>Pallet labeling, track &amp; trace</li> <li>Warehouse tags for shelving and totes</li> <li>Product labeling, shelf labeling, apparel hang tags</li> </ul>	<ul> <li>Items stored outdoors (lumber, brick, steel)</li> <li>Continuous media used in mattresses &amp; pillows</li> <li>Items that withstand extreme temperatures</li> <li>Items used in chemical environments</li> <li>Clothing care labels that withstand washer/dryer</li> </ul>

## SATO AMERICA CORPORATE

14125 South Bridge Circle Charlotte, NC 28273 Phone: (704) 644-1650 sales-sal@sato-global.com LABEL MANUFACTURING, SERVICE & SALES UNITED STATES MEXICO CANADA

## www.satoamerica.com

©2021 SATO America. All rights Reserved. Rev B • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.