



TECSX5
TXPSX5

5" media width

10" media width



Thermal Transfer Printers | 306 dpi



TXPSX5



TECSX5

Industry-Leading Thermal Transfer Printers

TECSX5

The TECSX printers are ideal for tags, labels and signs up to 5" wide at speeds up to 10 ips. Utilizing the End-To-End Slip-On® tags, various pot tags, and pressure sensitive signs makes this the most versatile printer for the money on the market. USB and Ethernet connectivity are available as options.

TXPSX5

The TXPSX printer provides utility above and beyond its price tag at speeds up to 8 ips. This printer can easily handle tag widths up to 10" ladderstyle (sideways). This print orientation promotes faster throughput and maximum ribbon usage. The rugged powder coated industrial strength steel case is designed for harsh environments, and is still attractive for office and store settings.

Streamlined Features

- FETHR Head (Floating Edge Type Head Revolution)
- Fast to Load Label & Ribbon Path
- Print Media Thickness up to 24 mil
- Standard Ribbon Save
- Standard Parallel and Serial Ports
- CE Approved
- Warranty Included
- Fast and Easy Handling
- High Speed Printing
- High Quality Print Technology



GENERAL SPECIFICATIONS

TECSX5 | TXPSX5

PRINTER MODEL	TECSX5		TXPSX5	
PRINT SPECIFICATIONS				
Printing Method	Direct Thermal/Thermal Transfer			
Print Resolution	306 dpi (12 dots/mm)			
Maximum Print Speed	10 ips		8 ips	
Maximum Print Area	5.02" (127.5 mm) W x 59" (1498 mm) L			
MEDIA SPECIFICATIONS				
Media Type	Die cut or continuous, Roll-fed			
Adjustable Sensing	Die cut, black mark, notched, hole punched			
Media Width Range	1.2" - 5.5" (30 to 140 mm)		2" - 10" (50.8 mm - 229 mm)	
Media Thickness	5.1 - 24 mil			
Ribbon Length	1,968 feet (600 m)			
Ribbon Save Mode	Standard			
Internal Roll Capacity	Material or media maximum O.D. 7.9 in (200 mm) / Minimum I.D. 3 in (134 mm)			
MEMORY/PROCESSING				
Main Memory	16 MB DRAM / 4 MB Flash			
CPU	32-bit RISC			
INTERFACES				
Standard	USB, Serial (RS-232C), ECP (Centronics Parallel)			
Optional	Ethernet			
FONT/BARCODE SYMBOLOGIES				
Character Types	Alphanumeric, symbols, and special characters			
Resident Fonts	21 Bit Map, 7 Outline & 132 Writable Character Types, Optional Time Type			
Barcode Types	UPC/EAN/JAN, Code 39, Code 93, Code 128, NW-7, Industrial 2of5, ITF, Postnet, RSCC, KiX-Code			
Graphics	Printing in 1 dot is possible			
Lines	Vertical/horizontal/diagonal			
Character/Barcode Orientation	0, 90, 180, and 270 degrees			
OPERATING & ENVIRONMENTAL				
Power Consumption	100/240V: 3.0/1.3A, 144/142W			
Power Supply	120 - 240 V, 50 - 60 Hz			
Operating Temperature	40°F - 104°F (5 - 40° C), R.H. 25 - 85% Non-condensing			
Dimensions	11.5" (291 mm) W x 18.11" (460 mm) D x 12" (308 mm) H		15.75" (400 mm) W x 18.0" (457 mm) D x 12.5" (317.5 mm) H	
Shipping Weight	42 lbs (19 kg)		53 lbs (24.1 kg)	
Casing	Powder-coated industrial strength steel			
Display	20 x 1 LCD Display, 3 LEDs & 3 Keys			
Safety Standards	CE, US, CSA, and FCC Class A			
ACCESSORIES & OPTIONS				
Optional Accessories	UHF RFID			

**SATO AMERICA
CORPORATE**
14125 South Bridge Circle
Charlotte, NC 28273
Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES
UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com/hort

©2015 SATO America. All rights Reserved. RevF • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.