



## CS-9018 Cutter/Stacker

Laser Printer Accessory



# CS-9018

**Fast. Reliable. Time-Saving Convenience.**

### Streamlined Features

- Self-contained, continuous form ticket handling
- Slit, cut & sequentially stack tickets at 235,000 per hour<sup>1</sup>
- Automatic top-of-form registration
- 2-line, 40-character LCD display
- Double-cut capability for clean-edge tickets
- Up to 59 feet per minute<sup>2</sup>
- Variable speed capability<sup>3</sup>
- Stores up to 99 ticket configurations
- Removable/interchangeable slitter assemblies
- Operator-friendly controls
- Quick & easy batch separation
- Increased productivity
- Automatic time-out circuit
- Cross cut knife and slitter assemblies easily replaced by user to maintain production

### Industry Applications

- Apparel Tags
- Price Labels
- Furniture Tags
- Routing Labels
- Mailing Labels
- Shelf Labels

<sup>1</sup> Requires optional slitter assembly

<sup>2</sup> Dependent on ticket length

<sup>3</sup> Model year 2020 and later up to 36% faster

# GENERAL SPECIFICATIONS / CS-9018

STOCK SPECIFICATIONS			
Media Size	Width	6-18 inches (152.4-457 mm) / Pin feed 0.5 inches (12.7 mm) per side	
	Thickness	Maximum 20 mil	
Ticket Size <sup>4</sup>	Length	2-4.5 inches (51 - 114.3 mm)	
	Width	1.25-3.5 inches (31.75 - 88.9 mm) <i>Special order minimum of 1.0" (25.4 mm)</i>	
Stacker Capacity		38 inches (965.2 mm) or approximately 3,500 tickets @ 11 mil	
THROUGHPUT (Variable - dependent on speed selection, ticket length and number across)			
Tickets Per Hour	5 Across	47,000 <sup>5</sup> tickets per hour @ 3 inches x 4.5 inches (76.2 mm x 114.3 mm)	59 ft/min
	11 Across	116,000 <sup>5</sup> tickets per hour @ 1.5 inches x 3.5 inches (38.1 mm x 88.9 mm)	51 ft/min
	13 Across	153,000 <sup>5</sup> tickets per hour @ 1.25 inches x 2.75 inches (31.75 mm x 69.9 mm)	44 ft/min
	17 Across	227,000 <sup>5</sup> tickets per hour @ 1 inch x 2 inches (25.4 mm x 50.8 mm)	36 ft/min
LCD DISPLAY			
Format		2 lines, 40 characters	
Content		Ticket count, speed and throughput	
Configurations		Up to 99 programmable ticket configurations	
Error Messages		Full array of error messages: JAMS, STACKER FULL, COVER OPEN, PAPER OUT	
Language Support		English, Spanish, Italian and German	
SAFETY FEATURES			
Auto System STOP		Activated if protective covers are not in place, paper out, stacker full or ticket jam	
Manual STOP Switch		Manual and Emergency STOP Switches	
ELECTRICAL/ENVIRONMENTAL/PHYSICAL			
Power Supply		220 VAC/60 Hz, single phase 20 AMP	
Acoustic		78 Dba	
Dimensions		78 inches (1981.2 mm) W x 31 inches (787.4 mm) D x 43 inches (1092.2 mm) H	
Weight		462 lbs (209.5 kg)	
OPTIONS			
Slitter		Interchangeable slitter modules, including special design for small width of 1-1.5 inches (25.4 - 38.1 mm)	
Control		Loop control for inline operation, feed with stop / start as input loop varies	
Waste Collection		Additional waste collection bins for quick swap	
Knives		Replacement and refurbished cross cut and slitter assemblies available for operator replacement	

<sup>4</sup> The recommended ticket size is a ratio where the length is greater than 1.3 times the width.

<sup>5</sup> Model year 2020 and later

## SATO AMERICA CORPORATE

14125 South Bridge Circle  
Charlotte, NC 28273  
Phone: (704) 644-1650  
sales-sal@sato-global.com

## LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA  
CANADA CARIBBEAN

[www.satoamerica.com](http://www.satoamerica.com)

©2020 SATO America. All rights Reserved. Rev L • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.