

# SATO-Direct 200CT

## FACESHEET

Basis Weight (lb/ream)	47.2
Caliper Target (mils)	3.1
Tensile MD Target (lb/in)	37
Tensile CD Target (lb/in)	17
Tear MD (grams)	45
Tear CD (grams)	
Stiffness MD (grams)	90
Stiffness CD (grams)	35
Color	White

## ADHESIVE

Description	Acrylic Cold Temperature
Caliper Target (mils)	0.6

## LINER

Description	40# SC
Caliper Target (mils)	2.4

## TOTAL CALIPER

Caliper Target (mils)	6.1
-----------------------	-----

## ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	-20		
Service Temperature (°F)	-65	to	120

## SPECIAL NOTES:

## FACESHEET TYPE

- ✓ Paper
- Film

## PRODUCT TYPE

- ✓ Label
- Tag
- Receipt

## IMAGING CAPABILITY

- ✓ Direct Thermal
- Thermal Transfer - Wax
- Thermal Transfer - Wax/Resin
- Thermal Transfer - Resin
- Laser

## AGENCY RECOGNITION

- UL
- cUL
- ✓ FSC
- ✓ FDA.21 CFR 175.105
- BPA Free

## MAXIMUM OUTDOOR LIFE

- ✓ For Indoor Use only
- <6 months
- <12 months
- <18 months
- 2 years

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

## SATO AMERICA

**CORPORATE**  
 14125 South Bridge Circle  
 Charlotte, NC 28273  
 Phone: (704) 644-1650  
[sales-sal@sato-global.com](mailto:sales-sal@sato-global.com)

**LABEL MANUFACTURING, SERVICE & SALES**  
 UNITED STATES MEXICO CENTRAL AMERICA  
 CANADA CARIBBEAN

