

SATO-Direct 225CT

FACESHEET

Basis Weight (lb/ream)	50
Caliper Target (mils)	3.2
Tensile MD Target (lb/in)	35
Tensile CD Target (lb/in)	14
Tear MD (grams)	50
Tear CD (grams)	55
Stiffness MD (grams)	
Stiffness CD (grams)	
Color	White

ADHESIVE

Description	Rubber Cold Temperature
Caliper Target (mils)	0.7

LINER

Description	Glassine
Caliper Target (mils)	1.6

TOTAL CALIPER

Caliper Target (mils)	5.5
-----------------------	-----

ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	-10		
Service Temperature (°F)	-65	to	120

SPECIAL NOTES:

Offers a thin liner allowing additional labels per roll.

FACESHEET TYPE

- ✓ Paper
- Film

PRODUCT TYPE

- ✓ Label
- Tag
- Receipt

IMAGING CAPABILITY

- ✓ Direct Thermal
- Thermal Transfer - Wax
- Thermal Transfer - Wax/Resin
- Thermal Transfer - Resin
- Laser

AGENCY RECOGNITION

- UL
- cUL
- FSC
- FDA.21 CFR 175.105
- ✓ BPA Free

MAXIMUM OUTDOOR LIFE

- ✓ For Indoor Use only
- <6 months
- <12 months
- <18 months
- 2 years

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

9007033

SATO AMERICA

CORPORATE
 14125 South Bridge Circle
 Charlotte, NC 28273
 Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES
 UNITED STATES MEXICO CENTRAL AMERICA
 CANADA CARIBBEAN

www.satoamerica.com

©2021 SATO America . All rights Reserved. • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

10/18/2021