



- Print speeds up to 12 ips (format & carrier dependent)
- Prints on a wide variety of media
- High smudge & scratch resistance
- Prints at moderate print head energy heat settings

## TECHNICAL DATA

RIBBON PROPERTY	
Base Material	Polyester Film
Ink Color	Black
Transmission Density	1.95
Back Coating	Yes
Total Thickness	Black < 9 µm Anti static build-up treated
PET Thickness	4.5 µm
Optical Density	≥ 2.1 D
Ink Melt Point	185°F (85°C)
Recommended Substrates	Coated and uncoated paper, tag stocks, and synthetics
DURABILITY OF PRINTED IMAGE	
Smudge & Scratch Resistance	High
Storage Condition	40°-90°F (5-35°C), 20-85% RH
Storage Life	1 year after manufacturing

Inventory, Shipping, Pharmaceutical, Cosmetics, Shelf-edge, Markdown, Lawn and Garden, Ingredient, Food Rotation, Work In Process, Rating Plates, Retail Labeling, Care Labels, Signage & Logos, Laboratory, Healthcare, Tags, Short Term Outdoor Applications, Conveyor Sorting, Chemical Drums

**Please contact us if your application is not among these.**

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

9007039

